

PATENT

TITLE: IMPROVED HIGH INTENSITY LIGHT SOURCE

This application claims the benefit of the following U.S.

- 5 Provisional Applications: U.S. Provisional Application Nos. 60/192,731
 filed March 27, 2000; 60/224,059 filed August 9, 2000; 60/224,298 filed
 August 10, 2000; 60/224,290 filed August 10, 2000; 60/224,291 filed
 August 10, 2000; 60/224,257 filed August 10, 2000; 60/224,289 filed
 August 10, 2000; 60/224,866 filed August 11, 2000; and 60/234,415 filed
 10 September 21, 2000. All of these provisional applications are hereby
 incorporated by reference in their entireties.

Field Of The Invention

- 15 The present invention is directed generally to high intensity light
 sources and more particularly to plasma light sources for use in
 applications such as projection systems based on reflective
 microdisplays.

Background Of The Invention

- 20 There is a continuing need for long-lived, efficient, compact, and
 high intensity white light sources for applications such as projection-
 based televisions and computer monitors as well as movie screen
 projectors. The various kinds of light sources which have been used
 previously include arc lamps and plasma lamps. Although an arc lamp
 25 produces an intense light by maintaining an electric arc between two
 electrodes, arc lamps have not tended to be long-lived for at least two
 reasons. First, the electrodes between which the arc is formed
 inevitably deteriorate and erode during the operation of the arc lamp,
 and ultimately this erosion leads to lamp failure. Second, arc lamps
 30 conventionally employ an envelope or bulb made from a transparent

PATENT

material in order to contain the gas fill of the lamp. Quartz has conventionally been used for such bulbs or gas envelopes.

Quartz bulbs, however, have several disadvantages. Because quartz devitrifies or recrystallizes at elevated temperatures, quartz bulbs do not endure well the high temperatures and repeated heatings inherent in lamp operation, and they tend to eventually discolor or crack causing lamp failure and limiting the useful life span of the lamp. In addition, because quartz has a low thermal conductivity, the use of the quartz bulb limits the maximum operating temperature of the lamp, and, therefore, the maximum obtainable brightness. Furthermore, quartz is partially permeable so that gas tends to slowly diffuse out of the bulb envelope. Ultimately, this diffusion causes the lamp to fail.

Unlike arc lamps, plasma lamps do not rely on electrodes, but rather produce light by creating a plasma discharge in a gas contained in a bulb by exposing the lamp gas to intense radio wave or radio frequency radiation. (As used herein, the phrase "radio wave radiation", as well as the acronym "RF", is intended to encompass electromagnetic radiation frequencies in either the conventional radio frequency range or in the conventional microwave frequency range.) Although there are no electrodes to fail in the case of a plasma lamp, the transparent bulb that is conventionally used to contain the gas is also typically made of quartz and has the same disadvantages discussed above in connection with the arc lamp because of the high operating temperatures involved.

In order to mitigate the bulb failure problem, various mechanical cooling arrangements have been developed to rotate the bulb and to propel cooling air onto its outer surface during lamp operation. However, such mechanical arrangements are complex, expensive, and occupy space which is often a scarce resource in the intended application for the lamp. In addition, the presence of these mechanical arrangements compromises the ability to collect the light generated by the lamp, thereby reducing efficiency.

PATENT

Plasma lamps also conventionally require a separate mechanism to couple the radio wave radiation generated by the radiation source to the bulb filled with the plasma discharge-forming medium. The need for such a separate coupling mechanism is another problem with the plasma lamp because inefficiency of the coupling correspondingly constrains the overall efficiency of the plasma lamp. One conventional approach to such coupling is to mount the bulb near a separate air-filled RF structure, such as a waveguide, that receives the radio wave radiation from the radiation source and transmits the radiation to the bulb. In practice this approach may lead to a power loss as high as 60% because of coupling inefficiencies. In addition, the resulting structure is not physically compact because the RF structure is separate from the bulb.

Alternatively, it is known to mount the quartz bulb inside a separate structure and to place coils near to the bulb in order to inductively transfer radio wave radiation energy to the gas in the bulb. Again, however, the resulting structure lacks integration and compactness because the RF structure is separate from the bulb.

It is desirable to provide improved light sources that avoid these and other problems with known light sources, and it is to these ends that the present invention is directed.

Summary of the Invention

According to one aspect of the invention, a plasma lamp is provided that comprises a gas housing containing a plasma discharge forming medium, and a source of radio frequency energy coupled to the plasma discharge medium. The gas housing is constructed from ceramic material and has a window transparent to visible light.

In more specific aspects, the window may be a sapphire window. The invention greatly extends the operating life expectancy of the plasma lamp as compared with the prior art lamps which use quartz

PATENT

because the problems of quartz devitrification at high temperature and quartz gas permeability are eliminated.

According to another aspect of the present invention, the RF structure used for the radio wave radiation and the envelope used to
5 house the gas fill are formed so as to constitute a single, integrated ceramic structure.

According to another aspect of the present invention, solid material such as ceramic rather than air is used for the dielectric and the gas fill is contained by a combination of solid ceramic and a sapphire
10 window. In this way the separate gas envelope and air-filled waveguide structure employed in the prior art are replaced by a single, integrated structure.

Because the integration of the RF structure and the gas envelope permits the quartz bulb to be done away with entirely, plasma lamps
15 according to the present invention enjoy an unprecedented operating life expectancy as compared with the prior art. This is so in part because the problems associated with the inability of the quartz bulb to withstand heatings are eliminated.

In addition, the integrated design of the present invention enables
20 a much higher proportion of the radio wave radiation energy to be focused onto the gas fill. As a result, the plasma lamp according to the present invention is made much more efficient.

The present invention enables these and many other benefits to be obtained.

25

Brief Description of the Figures

Figure 1 is a side cross-sectional view of a gas housing for a plasma lamp according to a first embodiment of the invention.

Figure 2 is a side cross-sectional view of a plasma lamp
30 according to a second embodiment of the invention.

Figure 3 is a side cross-sectional view of a plasma lamp according to a third embodiment of the invention in which the gas housing is integral with a waveguide comprising a solid dielectric material.

- 5 Figure 4A is an end view of a plasma lamp according to a fourth embodiment of the invention in which the gas housing is integral with a waveguide comprising a solid dielectric material while Figure 4B is a side cross-sectional view of the same plasma lamp.

- 10 Figure 5 is a side cross-sectional view of a plasma lamp according to a fifth embodiment of the invention in which the gas housing is also integral with a waveguide comprising a solid dielectric material.

Figure 6 shows a process suitable for sealing a gas housing according to the present invention.

- 15 Figure 7 is a side cross-sectional view of an alternative embodiment of the plasma lamp of Figure 2.

Detailed Description Of Preferred Embodiments

- 20 Figure 1 shows a first embodiment of an improved light source in accordance with the invention. The light source may be a plasma lamp comprising a gas housing 20 preferably formed from a ceramic material 22, as will be described below, with an interior cavity or chamber 24 for containing gas. The housing may generally be rectilinear or cubic, and the chamber may be spherical. A channel 30 may connect the chamber
- 25 to an exterior surface 32 of the housing. The channel 30 may be made of light transmissive material, preferably of sapphire in order to form a window 34 for emitting visible light from the chamber. The window preferably has a generally tapered, conical shape; *i.e.*, a frusto-conical shape. The sapphire window seals the chamber to contain the gas,
- 30 while affording an exit for the light produced by the plasma discharge.

PATENT

Sapphire is preferred for the window since it is less gas permeable than quartz, for example, and better withstands the heat cyclings and high temperatures associated with lamp operation. Furthermore, the gas housing 20 is preferably made from a ceramic material, as described below, since ceramics are much more durable under heating than other materials such as quartz. As a result, the ceramic housing affords a much longer life expectancy for the plasma lamp than the conventional quartz bulb of the prior art. In addition, the ceramic housing advantageously enables the plasma lamp to be operated at a much higher maximum temperature than the quartz bulb, because it avoids the lower softening temperature point and low thermal conductivity limitations of quartz.

The sapphire window 34 may function as a "light integrator" for transmitting the light of the plasma lamp from the chamber, for example, to application-specific optics. The tapered, conical sapphire window 34 may be sealed against the surrounding ceramic material forming the channel 30 by coating the outside edges of the sapphire window with a material such as a glass containing MgO, or, alternatively, with SiO₃ or SiO₂. Next the mating surfaces of both the window and the ceramic channel may each be coated with a thin layer of metallic material, such as copper, a copper alloy, or platinum. Then a piece of preferably pure platinum wire may be placed between the two thin film layers. Finally, a laser is used to heat the wire, and thereby melt the metallic material and bond the layers together.

Alternatively, the coated sapphire window 34 may be sealed to the ceramic housing by heating a glass frit. In yet another alternative, the ceramic housing may be "shrunk down" onto the sapphire window during high temperature firing.

The gas fill in the plasma lamp according to the first embodiment of the invention can be coupled to a source of electromagnetic energy, such as radio wave radiation in any of a variety of ways in order to

PATENT

create a plasma discharge within chamber 24. Preferably this should be done so that the RF structure that is active with the radio wave radiation energy is integrated with the gas housing 20, as will be described.

5 The gas fill may appropriately be a combination of a metal compound and a carrier gas. The metal compound may preferably be a metal halide such as indium bromide. Other examples of suitable metal compounds are praseodymium and mercury. Preferred gases for the carrier gas are xenon, neon, argon, or krypton.

10 Figure 2 shows a second embodiment of a lamp in accordance with the invention which is somewhat similar to Figure 1 except that the gas housing has an integrated RF energy structure. In Figure 2, the elements are designated similarly to Figure 1, using like reference numerals for like elements. The gas fill chamber 24 may be housed in a gas housing 20 preferably comprising a ceramic material 22 and
15 provided with a light transmissive window 34, preferably of a tapered rod of sapphire and a fill plug 38 as previously described. In this embodiment, an RF energy structure such as one or more coils 36 may be formed within the ceramic housing. The coils 36 function to inductively couple radio wave radiation energy to the gas fill in chamber
20 24 in order to create the plasma discharge. In this way, the RF structure of the plasma lamp that is active with radio wave energy is integral with the ceramic housing 20 that contains the plasma gas fill. This integration of the RF structure of the plasma lamp and the gas housing into a single structure, as shown, improves the coupling of RF energy to
25 the gas, and allows significant gains in lamp efficiency and compactness.

The second embodiment may also comprise segments of ferrite material 41 placed adjacent the coils 36 in order to help concentrate the magnetic field associated with the coils 36 on the gas fill. An illustration
30 of this embodiment is shown in Figure 7.

PATENT

Figure 3 shows a third embodiment of a lamp in accordance with the invention which integrates both the gas housing and an RF energy source within the same structure. A gas housing 50 for the gas fill may be formed so as to be integral with a waveguide 52 which preferably
 5 comprises a ceramic structure having a substantially rectangular cross-section. Because no separate bulb is used, the housing 50 and waveguide 52 comprise a single, integrated structure. A source of radio wave radiation 54 may be disposed within the ceramic structure, for example, near one end of the waveguide. The RF source 54 may be an
 10 RF antenna, a probe, or the like for introducing RF energy into the waveguide. The gas housing 50 may be located near the other end of the waveguide, for example. As shown, the gas housing may further include a light transmissive window 56 connected to the end wall of the housing. The window is preferably made from sapphire.

15 The dimensions of the waveguide and the locations of the RF source and gas housing preferably are chosen so that the electromagnetic field produced by the radio wave radiation in the waveguide exhibits a maximum in intensity at or near to the location of the housing in order to optimize the energy coupling to the gas. The
 20 waveguide may form a resonant structure having a resonant mode at the frequency of the radiation from the RF source 54. The necessary relationship among the waveguide dimensions, dielectric constant, and RF frequency can be determined in a well-known way using electromagnetic waveguide theory. For example, it is well-known that
 25 for a rectangular waveguide cavity containing a dielectric with permeability and permittivity constants μ and ϵ , and having length, width and depth dimensions a , b , and d and metal boundaries, the frequencies $w(m,n,p)$ for the resonant modes are given by the following equation:

$$w(m,n,p) = (\mu\epsilon)^{-1/2} (m^2\pi^2/a^2 + n^2\pi^2/b^2 + p^2\pi^2/d^2)^{1/2}$$

30 where m , n , and p are integers.

PATENT

Furthermore, because the dimensions of the waveguide scale with the square root of the dielectric constant of the dielectric, use of a solid dielectric material instead of an air dielectric permits a dramatic reduction in waveguide size, particularly if a ceramic material with an appropriately high dielectric constant is chosen. The waveguide is preferably made from a solid ceramic material with a high dielectric constant (higher than air or greater than 1), such as titanium dioxide (TiO_2) or barium neodymium titanate. In practice, it is found that materials that exhibit a suitably high dielectric constant are typically porous and unable to provide the required hermicity to contain the gas fill. Accordingly, as shown in Figure 3, a liner 58 of a better hermetic ceramic, such as alumina (Al_2O_3), is preferably deposited along the inner boundary of the ceramic material that forms the gas housing. This liner 58 improves the sealing of the gas fill.

Figures 4A and 4B show a fourth embodiment of a light source in accordance with the invention. A gas housing 60 for the gas fill is formed so as to be integral with a cylindrical resonant waveguide structure 62 comprising ceramic material. Because a separate bulb is not used, the gas housing 60 and waveguide 62 comprise a single, integrated structure. A source of radio wave radiation 64 may be disposed near one end of the waveguide, while the gas housing is formed at an opposite end. The gas housing 60 may include a window 66 preferably made from sapphire.

As with the embodiment of Figure 3, the dimensions of the waveguide structure, the locations of the RF source and gas housing, and the frequency of the radio wave radiation source may be chosen so as to support resonant modes which optimize the RF energy coupling from the RF source to the gas housing. The gas housing 60 may, therefore, be appropriately located so that the housing receives a high level of radio wave radiation energy from the source 64.

PATENT

Figure 5 shows a fifth embodiment of the present invention. In this case the waveguide 72 may have a cross-section with a varying dimension, such as a varying profile rather than a rectangular cross-section in order to improve the matching of the impedance of the waveguide to that of a gas housing 70 in the waveguide. In turn, this improved impedance matching broadens somewhat the range of frequencies over which the waveguide forms a resonant structure so as to efficiently deliver power to the gas housing. As with the first embodiment, however, a separate bulb is not used so that the housing 70, waveguide 72, and radio wave radiation source 74 comprise a single, integrated structure. The dimensions of the waveguide and the locations of the radio wave radiation source and housing, may appropriately be chosen to produce a resonant mode that maximizes the energy coupled from the source to the gas housing for the operating frequency band of the source.

In other embodiments of the invention, the interior of the gas housing may be coated with a thin film of protective material such as MgO. The MgO will protect the inner surface of the gas housing from the spontaneous conversion of ceramic to elemental metal that sometimes occurs in the presence of a partial vacuum and high temperature. This effect is not desirable and may cause failure of the bulb. Because the film of MgO acts as a secondary electron emitter, the film can also add to the brightness of the plasma lamp.

In alternative embodiments of the invention, a bulb made from quartz or another suitable material may be retained as a structure which houses the gas fill, but the quartz structure is sized so as to fill the interior space in the ceramic gas housing, which ceramic gas housing may be integrated into a ceramic waveguide as described above. This variation can be utilized in conjunction with any of the embodiments of the invention shown in Figures 1-5 by expanding the bulb into the interior of the ceramic gas housing with a heating process. One possible heating

PATENT

process is to electrically overdrive the bulb. Alternatively, the outer surface of the quartz bulb may be ground so as to fit closely into the ceramic gas housing or integrated ceramic gas housing and waveguide structure.

- 5 An example of a waveguide structure according to these alternative embodiments is a rectangular waveguide structure having dimensions of 34.72 mm by 38.84 mm by 17.37 mm and composed of alumina (Al_2O_3) ceramic. For such a waveguide, the RF structure, e.g., antenna, may appropriately be driven at a frequency of 2.4 gigahertz
10 (GHz) in order to efficiently couple radio wave radiation of that frequency to the gas fill in the quartz bulb within the waveguide.

- When the plasma lamp is constructed in such a way, the heat produced by the bulb operated in the normal drive mode will be dissipated more uniformly and rapidly than in the prior art because of the
15 tight fit between the quartz bulb and the surrounding ceramic. In this way the ceramic encasing the quartz bulb acts as a heat sink and ameliorates the problems associated with the heating of a quartz material.

- These alternative embodiments having a quartz bulb can be improved by depositing a thin, non-conductive reflective coating on
20 either the inside or outside walls of the quartz bulb. The reflective coating can be deposited by evaporation, spraying, painting or other method and should cover the bulb apart from an "exit" window for the light. The material used may be liquid bright platinum or a similar
25 reflective material. The function of the coating is to improve upon the reflectance of the ceramic and thereby increase the brightness yielded by the lamp.

- In other embodiments of the invention, the bulb for containing the gas fill may be made entirely from sapphire rather than quartz. Sapphire
30 is transparent to visible light and can better withstand high temperatures than quartz. Sapphire is also less permeable than quartz. Accordingly,

PATENT

the use of sapphire for the bulb can significantly improve the performance of the plasma lamp as compared with the prior art quartz bulb lamp.

5 A method for constructing a representative embodiment of the ceramic gas housing for the fill gas of the plasma lamp will now be described with reference to Figure 6. The first step in this method is to fabricate the housing 80 as by pressing ceramic into a mold. A small fill hole 40 may be left in one end of the housing. A sapphire window 84 is then sealed to the other end of the housing. The ceramic housing may
10 then be placed in a vacuum chamber. An appropriate metal halide material may then be put into the enclosure through the fill hole 40. Next, the vacuum chamber can be pumped down. After the proper subatmospheric pressure is reached, the chamber can then be backfilled with an excitation gas.

15 The excitation gas is allowed to backfill until the chamber and, hence, the ceramic housing reaches the desired pressure. A ceramic plug 85 may then be used to seal the fill hole in a manner discussed more fully below in connection with Figure 6. After the fill hole is sealed in such a manner, the lamp is then removed from the vacuum system
20 and tested.

Figure 6 illustrates an improved sealing procedure that is useful for making plasma lamp gas housings according to the present invention. In particular, it has been found that a tapered fill hole 40 and a matchingly tapered plug 85 provide a stronger seal than a straight-
25 edged fill hole and matching plug. The actual seal between the hole and the plug is made with a glass frit or a ceramic material 82. The seal is formed by suitably heating the fill hole region such as by using laser light 86. The use of laser light is advantageous because it allows the sealing process to be conveniently accomplished while the plasma gas housing
30 is still in the vacuum chamber immediately after the fill material has been added. Furthermore, lasers are especially well suited for this

PATENT

application which requires the quick heating of a small region to a high temperature.

The scope of the present invention is meant to be that set forth in the claims that follow and equivalents thereof, and is not limited to any of
5 the specific embodiments described above.

10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2